

S.O GEAR OIL XEP

MILD EP AUTOMOTIVE GEAR OIL

DESCRIPTION

S.O GEAR OIL XEP is mild EP automotive gear oil formulated with sulphur-phosphorus extreme additives and meets the performance requirements of API GL-4, MIL-L-2105B and CS 3000A. The oil is environmental friendly, containing neither lead nor-chlorine. Exhibits outstanding wear protection, anti-rust, anti-corrosion, excellent demulsifiability and foaming resistance properties.

CHARACTERISTICS

- Superior oxidation and thermal stability
- Outstanding protection against wear and shock
- Excellent rust and corrosion inhibition
- Good load-carrying capability
- Prolongs gear equipment life

APPLICATION

S.O GEAR OIL XEP is suitable for all gears in passenger cars and other automotive transmission systems operating under moderate to severe conditions.

TYPICAL SPECIFICATION

SAE GRADE		85W/140
Kinematic Viscosity, cSt		
@ 40oC	ASTM D445	428
@ 100oC	ASTM D445	31
Viscosity Index	ASTM D2270	99
Flash Point (COC), oC	ASTM D92	235
Pour Point, oC	ASTM D97	-20

Version 03/21



AP Oil Pte. Ltd.
A member of AP Oil Int'l Ltd

18 Pioneer Sector 1, Jurong, Singapore 628428
tel 65 6861 5503 fax 65 6861 9162

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.