

## S.O. X-SUPERSTAR SS HEAVY-DUTY DIESEL ENGINE OILS

### DESCRIPTION

**S.O. X-SUPERSTAR SS** is a high performance, high TBN heavy duty diesel engine oil formulated primarily for normally aspirated or turbo charged diesel engines under most severe operating conditions. The oil meets the specification requirements of API CF/SF, CF-2, MIL-L-2104D, Caterpillar TO-2, etc.

### CHARACTERISTICS

- High thermal and high oxidation stability
- Good detergency and dispersancy properties
- Effective control of piston deposits, wear and corrosion
- Keeps engine clean
- Extends oil drain interval
- Prolongs engine life

### APPLICATION

**S.O. X-SUPERSTAR CF SS** is recommended for naturally aspirated, turbocharged or supercharged diesel engines of heavy duty vehicles, commercial trucks and construction machineries as well as stationary diesel engines.

### TYPICAL SPECIFICATION

<b>SAE GRADE</b>		<b>30</b>
Kinematic Viscosity, cSt		
@ 40oC	ASTM D445	100
@ 100oC	ASTM D445	11.3
Viscosity Index	ASTM D2270	98
Flash Point (COC), oC	ASTM D92	230
Pour Point, oC	ASTM D97	-10
TBN, mgKOH/gm	ASTM D2896	10

Version 03/21



**AP Oil Pte. Ltd.**  
A member of AP Oil Int'l Ltd

18 Pioneer Sector 1, Jurong, Singapore 628428  
tel 65 6861 5503 fax 65 6861 9162

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.